

Distributed by: Laguna Clay Company 14400 Lomitas Ave City of Industry, CA 91746 1-800-4Laguna info@lagunaclay.com www.lagunaclay.com

Material Safety Data Sheet



Product Name

FRIT 085-A

Note: Do not leave fields blank. IF some point does not apply or is not specified, must be identified as follows: N / A: Not Applicable N / S: Not Specified

Section I: Identification of the Manufacturer

| Name of Manufacturer | In an emergency call: |
|---|--------------------------------|
| MACESA Fritas | (01152) 81 24 81 99 |
| Address: | For Information call: |
| BOULEVARD DIAZ ORDAZ Km. 335.5 GARZA GARCIA, N.L. MEXICO CP 66230 | (01152) 81 24 82 34 |
| | Preparation date: 8/19/2010 |
| | Sign |
| | |

Section II: Hazardous Ingredients

| Component Name | | No. CAS | Concentration (%) | OSHA PEL (mg/m3) | ACGIH TLV (mg/m3) | Other Limits Recommended |
|----------------|------------------|------------|-------------------|---------------------|----------------------|-----------------------------|
| 1 | Lead Monoxide | I3 17-36-8 | 30-35 % | 0.05 | 0.05 | N/E |
| 2 | Feldspathic Sand | 68476-25-5 | 65-70 % | 10 / %SiO2 +2 | 0.05 | 0.05 |
| 3 | | | | | | |
| 4 | | | | | | |

Section III: Physical and Chemical Characteristics

| Boiling point | N/A | Specific Gravity (H2O = 1) | 3.81 grs/cc | |
|-------------------------|-----|--------------------------------------|-------------|--|
| Vapor Pressure (mmHg) | N/A | Melting point | N/E | |
| Vapor Density (Air = 1) | N/A | Evaporation Ratio (butylacetate = 1) | N/A | |
| Water solubility: | | Appearance and Odor: | | |
| Insoluble | | Powder, odorless. Color may vary. | | |

Section IV: Fire and Explosion

| Flash Point (include method of determining) | Flammability Limits | Inferior | Superior |
|---|---------------------|----------|----------|
| N/A | | N/A | N/A |
| Extinguishing Media | | | |
| No danger of fire | | | |
| Special procedures for fire fighting | | | |
| No danger of fire | | | |
| Unusual danger and explosion | | | |
| Not required | | | |
| | | | O+D15 |

Section V: Reactivity

| Unstable | N/A | Conditions to avoid | | |
|--|--------|--|--|--|
| Stable | Stable | Avoid contact with acids (eg, acetic, hydrofluoric, etc.). | | |
| Incompatibility (Materials to Avoid) Avoid contact with acids (eg, acetic, hydrofluoric, etc.). | | | | |
| Hazardous Decomposition Products: | | | | |
| Under normal conditions, this product does not release after the application materials | | | | |
| Hazardous Polymerization: | N/A | Conditions to avoid N/A | | |
| 1 | | | | |

Section VI: Health Hazards

| Route.of.Entry | Inhalation | NO | Skin | SI | Ingestion | NO |
|--|--------------------|-----------|--------------------|------------------|-------------------|-----------|
| Health Hazards (Acute and Chronic) | | | | | | |
| | | | | | | |
| Acute: Improper handling of chips, without | the appropriate Pl | PE, can c | ause small lesions | s in contact wit | h skin and eyes | |
| Chronic: Excessive inhalation of respirable crystalline silica can cause silicosis. | | | | | | |
| The International Agency for Research on Cancer (IARC) concluded that there is evidence in humans for the carcinogenicity of crystalline silica in the forms of quartz from occupational sources. | | | | | | |
| Cancer risk | NTP? | YES | IARC Monograph | <u>YES</u> | OSHA Regulated | YES |
| Symptoms of Exposure Excessive exposure to dust from the chip without the proper PPE, may irritate eyes, skin and respiratory tract | | | | | | |
| Medical conditions aggravated by exposure Workers with poor respiratory capacity should have limited exposure to this material. | | | | | | |
| Emergency procedures and first aid. Skin: Wash with soap and clean water to the affected area Inhalation: Remove the person from exposure, moving to a place with clean, fresh air, if breathing has stopped, provide artificial respiration. Ingestion: Get immediate medical attention Eyes: Remove the person from exposure and flush the eye with large amounts of clean water, lifting the upper eyelid and down the bottom | | | | | | |
| Laguna Clay Company w | ww.Lagunad | lay.co | om 1-800- | 4Laguna | info@Lagun | aclay.com |

Section VII: Procedures for safe handling and use

Procedure in case of spills

Use appropriate PPE. Do not dry sweep, proceed to your collection, with a practice that eliminates the generation of dust (which may

Disposal method

Place material in suitable containers, identified and provided in accordance with federal, state and local

Precautions for handling and storage

NOT REQUIRED

Other Precautions

Use appropriate gloves to work with frit

Section VIII: Personal Protective Fauinment

Respiratory Protection (Specify Type) NOISH approved dust and mist

Ventilation:

Use adequate ventilation to maintain dust exposure below recommended limits. Avoid breathing dust. The greatest potential for exposure to

Eyes:

Use safety glasses or goggles. Do not use contact lenses in work areas.

Sikin:

Use cotton gloves or skin to minimize exposure of the skin. Wash hands with soap and water before eating, drinking, smoking and end of Other clothing and equipment

Note: Personal protection information indicated in this document is based on general information under normal conditions. Where special

Section IX: Regulations

SARA Report

N/A

Regulations for the Transportation (DOT)

This material is considered as non-hazardous for ground transportation and / or Air

(TSCA)

The components of this product have been introduced in the U.S. trade and are listed in the inventory of TSCA (Toxic Substance Control

Laguna Clay Company www.Lagunaclay.com 1-800-4Laguna info@Lagunaclay.com